




# PRODUCT DIMENSIONS & SPECIFICATIONS

## DX-TREME CS SERIES DEDICATED HORIZONTAL COILS



### STANDARD SPECIFICATIONS

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Liquid line - 3/8" ODS, suction line - 3/4" ODS on 1-1/2- 3 ton & 7/8" ODS on 3-1/2 - 5 ton.
- Inlet and outlet dimensions are identical (without end caps).
- Externally mounted flowrater body with Schrader valve for hiss-testing or internally mounted factory-installed TXV.
- Refrigerant lines exit from the top of the coil.
- Split access doors on top of the coil for easy service.
- Embossed galvanized cabinets standard.
- Top, bottom, and side flanges for furnace connection
- Fully insulated cabinets with faced insulation.
- Heavy duty plastic drain pan with four 3/4" FPT galvanized condensate drains (two per side).
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22 and R-410a when proper metering device is used.
- Ten-year limited warranty with registration

Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

COIL MODEL	R410a PISTON SIZE	DIMENSIONS			SHIPPING INFORMATION		
		CABINET WIDTH [W]"	CABINET DEPTH [D]"	CABINET HEIGHT [H]"	SHIPPING WEIGHT (LBS)		SKID QTY
					2 ROW	3 ROW	
CS24A*	0.055	19-1/2	31	15	35	45	16
CS24B*	0.055	19-1/2	31	19	39	50	16
CS24C*	0.055	19-1/2	31	23	47	61	16
CS30A*	0.059	19-1/2	31	15	40	52	16
CS30B*	0.059	19-1/2	31	19	39	50	16
CS30C*	0.059	19-1/2	31	23	47	61	16
CS36A*	0.068	19-1/2	31	15	45	58	16
CS36B*	0.068	19-1/2	31	19	45	58	16
CS36C*	0.068	19-1/2	31	23	47	61	12
CS42A*	0.074	19-1/2	31	19	52	66	16
CS42B*	0.074	19-1/2	31	23	55	71	16
CS42C*	0.074	19-1/2	31	25	52	66	12
CS48A*	0.08	19-1/2	31	23	63	81	12
CS48B*	0.08	19-1/2	31	25	60	78	12
CS60A*	0.089	19-1/2	31	23	103	132	12
CS60B*	0.089	19-1/2	31	25	104	133	12

Phone: 281.441.6500  
Toll Free: 800.423.9007  
Fax: 281.441.6510  
[www.aspenmfg.com](http://www.aspenmfg.com)



\* For complete warranty details visit [www.aspenmfg.com](http://www.aspenmfg.com).